



Bona[®] Conditioning Pads

Ensures optimum bonding of finishes and the smoothest possible final coat



The Bona[®] Conditioning Pad is designed for use on waterborne finishes but works equally well on solvent-based finishes. The conforming nature of the pads makes them ideal for most wood floor finish surfaces ensuring optimum bonding and the smoothest possible final coat. Bona Conditioning Pads are used with Siafast Delta Sheets for additional abrasion to eliminate grain raise.

- Abrades finish surfaces thoroughly for uniform appearance and good adhesion
- Will not leave unsightly scratches/swirls
- Will not mark or burn the finish surface
- Cleans easily by vacuuming
- 320-grit Bona Conditioning Pad, 150-grit Delta sheet
- 16" and 20" diameter



Bona[®] Conditioning Pads

Ensures optimum bonding of finishes and the smoothest possible final coat

RECOMMENDED USE

Intercoat abrasion for sealers and finishes.

Excellent for cleaning floor prior to recoat

DIRECTIONS

This Conditioning Pad from Bona is the new standard for surface conditioning of waterborne and solvent-based sealers and finishes. It is ideal for deburring, cleaning and smoothing wood floor sealers and finishes prior to the application of additional coats. When used on waterborne sealers with Siafast Delta Sheets, a smooth surface is prepared for finish coats while controlling grain raise. Two Pads can be used under the buffer. This allows air to circulate and helps eliminate friction heat that contributes to gumming and loading of the Bona Conditioning Pad and the SIAFAST Delta Sheets.

ORDERING INFORMATION

Bona Conditioning Pads				
Item	Size	Grit	No./Case	Lbs./Case
AAS19522203	16"	320	10	4
AAS19522101	20"	320	10	4
Siafast Delta Sheets				
Item	Size	Grit	No./Case	Lbs./Case
AA0001027	n/a	150	1, 10 pack	3.55
AAS19704303	n/a	150	50	0.55



Bona[®] Conditioning Pads

Ensures optimum bonding of finishes and the smoothest possible final coat