



Bona Recoat System[®]

Specifically designed to remove contaminants and prepare the floor for optimal adhesion of a



Prolong the life of a hardwood floor. The Bona Recoat System[®] is a proven process that eliminates recoat issues associated with the use of acrylic maintenance products. The floor is cleaned, contaminants are removed, and in less than a day, your customers can have a new coat of Traffic HD[®].

- Effectively removes acrylic maintenance coatings and other known contaminants while preparing the floor for an application of Bona Traffic HD.
- Works on all types of residential and commercial polyurethane-finished wood floors, including pre-finished, aluminum-oxide floors
- Great for floors with sanding limitations, like a thin wear layer.



Bona Recoat System®

Specifically designed to remove contaminants and prepare the floor for optimal adhesion of a

RECOMMENDED USE:

For use on polyurethane site-finished and pre-finished wood floors that have been maintained with acrylic maintenance products.

PRECAUTIONS:

Before using the Bona Recoat System on hand-scraped or distressed flooring, it is necessary to test the integrity of the existing finish. In an inconspicuous area, hand abrade a small section of flooring using a 220-grit screen or equivalent. If the abrasion completely removes the finish from high points, exposing raw wood and removing color, DO NOT PROCEED WITH THE BONA RECOAT SYSTEM.

DIRECTIONS:

Before application, protect surrounding areas using blue tape and plastic sheeting or towels to prevent possible staining from accidental contact with Bona Remove. In the event of a spill, immediately wipe up the affected area using a clean towel and water. 1. Pour a 4" wide line of Bona Remove along the starting wall. 2. Saturate the roller with product from the pour line. Set the roller down at the back side of the puddle and pull the roller towards you approximately 4-5 feet. Then, push back in the same path beyond your original start point. BE SURE YOU ARE USING THE RECOMMENDED COVERAGE OF 700-800 SQ. FT. PER GALLON. DO NOT SPREAD TOO THIN. DO NOT COVER MORE FLOOR THAN YOU WILL BE ABLE TO ABRASE AND CLEAN IN 20-30 MINUTES (APPROXIMATELY 200 SQ FT). 3. Using a 175-rpm rotary buffer equipped with the Bona Recoat Abrasive drive plate (replace it every 5000 to 7000 square feet of use), abrade the section of floor coated with Bona Remove—Abrade with the grain up and back over the same path. Start the next pass by overlapping the previous pass by 50%. 4. Hand-abrade any corners and sections missed by the buffer with 120-grit paper. 5. Using a window squeegee, squeegee Bona Remove

material from the wall. 6. Remove and clean all Bona Remove from the floor Using the Bona PowerScrubber® filled with Bona Deep Clean (refer to Bona Deep Clean directions for mixing instructions). 7. Repeat steps 1 through 6 until the entire floor has been treated. 8. TO ENSURE ALL CONTAMINATES HAVE BEEN REMOVED, IT IS RECOMMENDED THAT THE ENTIRE FLOOR BE PREPARED A SECOND TIME FOLLOWING STEPS 1 – 7 (DURING THE SECOND PASS, IT IS NOT NECESSARY TO HAND ABRASE). 9. Using a clean terry towel or microfiber cloth and warm water, wipe down the floor's perimeter, approximately 1" from the wall where the Bona PowerScrubber couldn't reach. It may also be necessary to wipe down all the baseboards and other areas the Bona Remove encounters. 10. Relocate buffer, Bona Recoat Abrasive drive plate, applicators, and all other equipment besides the Bona PowerScrubber, and remove from the floor. Thoroughly clean with water the Bona PowerScrubber brushes, squeegees, power cord, and your shoes/work boots of any remaining Bona Remove. Perform a final rinse on the floor using the Bona PowerScrubber and Bona Deep Clean. This step will help ensure the floor is clean of any Bona Remove due to footprints or missed areas during the initial steps. 11. Wet tack the entire floor with water. 12. Allow the floor to dry, and following label instructions, apply one coat of any Bona Traffic HD® family of finishes. If a second coat of finish is needed, Intercoat abrasion is not required. If an Intercoat abrasion is necessary, only abrade with a 320-grit Bona Conditioning Pad. The Bona Recoat process temporarily weakens the finish system and aggressive abrasion could cause damage to the total finish system.

CLEAN-UP:

Clean all tools and equipment with warm water.



Bona Recoat System[®]

Specifically designed to remove contaminants and prepare the floor for optimal adhesion of a

DISPOSAL:

Empty the Bona Power Scrubber recovery tank into a sewer line, such as a toilet or utility sink. Do not empty the contents into a vanity or kitchen sink, as the contents may plug the sink's trap

STORAGE:

Nonflammable—Bona Remove should be stored in a climate-controlled environment. Keep from freezing. Do not store above 100° F.

ORDERING INFORMATION:

Item #	Description	Size	No. Case	Weight/ Lbs.
WM772018201	Bona Remove	Gallon	2	18.45
WM760018001	Bona Deep Clean	Gallon	2	18.5