
Concrete Disc selector


Unterböden	Subfloor	 Part no. ASO312571	 Part no. ASO312582	 Part no. ASO312581
Beton weich	Soft concrete	+	O	O
Beton hard	Hard concrete	+	O	÷
Estrich	Screed	+	O	O
Anhydrite	Anhydrite	+	O	O
Densit	Densit	+	O	÷
Mörtelfliesen, Ton Ziegel	Tile mortar	O	O	+
Epoxy	Epoxy	+	+	O
Polyretahn	Polyurethane	÷	+	O
Klebstoff < 1mm	Glue thin < 1 mm	O	+	O
Klebstoff > 1mm	Glue thick > 1 mm	÷	O	+
Silan Klebstoffe	Silan Glue	÷	+	+
Asphalt (Bitumen, PEN max. 100)	Asphalt (Bitumen, PEN max. 100)	+	O	O
Bauxit	Bauxit	+	O	÷
Filzpappe	Cardboard	+	O	÷
Teppichschaum Rücken	Carpet foam	÷	O	+
Jute Rücken	Jute	÷	+	O
Filzreste untergründen	Felt rest-material	÷	O	O
Farbe	Paint	÷	O	+

+ : Beste Wahl / Best choice

o : Verarbeitbar / Usable

÷ : Nicht brauchbar / Not usable



	**Haben Sie das richtige Segment für die Aufgabe gewählt?** Bitte beobachten Sie die Abnutzung genau. Zum ersten Mal nach ca. einer halben Stunde. Tauschen Sie das Segment, wenn die Abnutzung ungewöhnlich ist.	**Have you chosen the right segments for the job?** Please monitor the wear of the segments closely. For the first time after approximately half an hour. Change the segments if the wear is unusually.
	**Fachgerechte Montage der PCD Maxi-Segmente** Bitte, PCD Oberkante rechts montieren in die gleiche Richtung wie die Drehung der Maschine.	**How to mount the PCD Maxi segments correctly** Please mount the PCD Maxi segment with the highest PCD point to the right in the same direction as the rotation of the machine.