Bona Mini Buffer

Compact oscillating machine for floor cleaning and maintenance

The Bona Mini Buffer is primarily designed for effective cleaning and maintenance of wooden floors in domestic environments. It is also suitable for stone, linoleum and other hard surfaces. Additional applications include abrading sealed floors before applying further coats of lacquer and buffing maintenance oil on oiled floors.



KEY BENEFITS

- Compact and lightweight
- Oscillating action makes the machine easy to operate
- Suitable for the maintenance of a wide range of hard floors

TECHNICAL DATA

Power supply	230 V / 50 Hz
Brush speed	1,500 1/min
Brush pressure	15 kg
Working width	33 cm
Theoretical area performance	990 m²/h
Clearance height	25 cm
Power cable length	7.5 m
Weight	9.4 kg
Protection class	I / IPX4
Sound pressure level	70 dBA
Dimensions (L / W / H)	31 x 31 x 113 cm

Bona Mini Buffer

Compact oscillating machine for floor cleaning and maintenance

DIRECTIONS FOR USE

Preparation: Sweep or vacuum the floor to remove abrasive grit, dust and dirt.
Cleaning: For general cleaning of sealed (varnished) wooden floors, fit a white or tan nylon pad. For intensive cleaning of particularly dirty floors, a red pad may be used.
Light sanding: Before applying additional coats of lacquer, place a sanding screen beneath a nylon pad fitted to the drive plate. Work systematically until the entire area has been treated.
Re-oiling: Apply oil with a brush, Pad or cloth. After the drying time specified for the product, buff with a white or red nylon pad. To remove remaining excess oil, place a cloth beneath the machine and buff the entire surface. Depending on the oil used, this may increase the final sheen. Always follow the instructions for the specific oil product.

SAFETY AND MAINTENANCE

- Switch off and unplug the machine before cleaning, maintenance, replacing parts or changing its application.
- Protect the power cable from damage. Do not use the machine unless the cable is in perfect condition.
- Never leave the machine standing on a cleaning pad or abrasive when not in use.
- Ensure that any chemicals used are suitable for the floor being treated. Clean splashes from the machine after use.
- Do not use the machine on gradients steeper than 2%.
- Repairs and service must only be carried out by Bona or an authorized distributor.