Bona Deck Guard

Technical data sheet

Finishing





An outdoor deck is constantly subjected to different elements of the weather, including harsh sunshine, and heavy rain and snow. Introducing Bona Deck Guard - a fast and convenient solution that keeps outdoor decks, exterior wooden structures & furnitures as good as new.

- Extra protection against mildew
- Low Odor
- Extremely low VOC content
- Latest UV Protection Technology
- Easy to Apply and Maintain
- High performance in any climate
- Outstanding UV protection
- Excellent physical wear characteristics
- Easy application, fast drying
- Superior adhesion & water repellency
- Excellent color & gloss retention
- Breathable finish
- Easy maintenance

Technical data

Physical Characteristics:
Ingredients – Polymeric resins, water, inorganic pigments, and propylene-based glycol ethers.
Colors – Brown & Neutral
Odor – Latex
Solids – approximately 30%
Gloss Level – Matt (approx 10% at 60°)
Density – 8.84 lbs/gal (1.060)
EU Regulatory VOC – <50 g/L
Stability – 3 years shelf life in unopened container

Application Characteristics:
Drying Time – 1-4 hours depending on surface. Dry time may increase for higher humidity climates.
Coverage – 6-12 sqm per Liter per coat at 1 mil wet film thickness, depending on the substrate
Application Tools – cut-in pad/applicator or brush, Bona Scrad Pad outfitted with 220-grit Bona Scrad Wings
Packaging – 1 Gallon plastic container

Recommended Use

- Composite Wood Decking
- Solid Wood Decking
- Exterior Wooden Structures and Furnitures

Directions

BEFORE USING, READ ALL DIRECTIONS AND SAFETY DATA SHEETS.

FOR TECHNICAL ADVICE: Call Bona US at 800-872-5515

COMPATIBILITY: Results may vary widely depending on the wood species, especially on oily and resinous exotic species. ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE AND DESIRED RESULTS.

RECOMMENDED APPLICATORS: Cut-in pad/applicator or brush, Bona Scrad Pad outfitted with 220-grit Bona Scrad Wings.

MIXING INSTRUCTIONS: SHAKE WELL BEFORE USING. DO NOT THIN.

APPLICATION FOR COMPOSITE WOOD DECKING: 1. Deep clean the surface to remove contaminants. 2. Let the surface fully dry. 3. Apply one coat of Bona Deck Guard using cut-in pad/applicator or brush. 4. Leave to dry for 1 to 2 hours. 5. Apply second coat of Bona Deck Guard using same method. 6. Leave to dry for 24 hours before using the decking.
7. If necessary, a third coat is recommended for higher durability.

APPLICATION FOR SOLID WOOD DECKING: 1. Deep clean the surface to remove contaminants and sand if necessary. 2. Apply one coat of Bona Deck Guard using cut-in pad/applicator or brush. 3. Leave to dry for 3 to 4 hours. 4. Remove grain-raise by buffing with Bona Scrad Pad outfitted with 220-grit Bona Scrad Wings. 5. Apply second coat of Bona Deck Guard. 6. Leave to dry for 24 hours before using the decking. 7. If necessary, a third coat is recommended for higher durability.

Maintenance

CLEAN UP: Clean application tools and equipment with water.

STORAGE AND DISPOSAL: Store at room temperature. Keep container closed when not in use. Do not store above 100˚ F (38˚ C). Do not transfer contents to other containers for storage and disposal. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Order Information

Item#	Size/Color	#/Case
WS740018002	Deck Guard - Medium Brown 1 Ga.	2
WS740018004	Deck Guard - Neutral 1 Ga.	2