



Bona CourtLines® Sport Floor Paint

OIL-MODIFIED WOOD SPORT FLOOR PAINT

Specially formulated for professional use on wooden sport floors



A high solids, solvent-based sport floor paint.

Bona CourtLines® Sport Floor Paint is for use with both waterborne and oil-modified sport floor sealers and finishes. Available in 15 primary colors and blendable to achieve an endless array of custom colors.

- Very low odor
- Low viscosity
- Fast drying with 24-hour recoat



Bona CourtLines® Sport Floor Paint

OIL-MODIFIED WOOD SPORT FLOOR PAINT

Specially formulated for professional use on wooden sport floors

TECHNICAL DATA

Ingredients:	Alkyd resins, odorless mineral spirits, pigments, driers, titanium dioxide
Flash Point:	100°F (37.8°C)
US Regulatory VOC:	< 490 g/L
Odor:	Solvent
Packaging:	Quart can, metal
Storage/Transport:	Store at room temperature. Keep container closed when not in use. Do not store above 100° F (38° C).
Application Tools:	Bona Nanoflock roller
Coverage:	125-150 square feet per quart
Leveling:	Excellent
Defoaming:	Excellent
Drying time:	24 hours (based on recommended coverage rate, under ideal conditions)
Disposal:	Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

BEFORE USING, READ ALL DIRECTIONS AND SAFETY DATA SHEETS. FOR TECHNICAL ADVICE: Call Bona US at 800-872-5515

HAZARD WARNING:

RAGS, STEEL WOOL OR WASTE SOAKED WITH BONA ALL COURT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED, WATER-FILLED METAL CONTAINER.

RESPONSE

In case of eye contact, flush immediately with water. Get medical attention if irritation occurs. For skin, wash thoroughly with soap and water. If affected by inhalation,

remove to fresh air. If swallowed, drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Get medical attention if symptoms.

Bona CourtLines® Sport Floor Paint

OIL-MODIFIED WOOD SPORT FLOOR PAINT

Specially formulated for professional use on wooden sport floors

RECOMMENDED USE

- Basketball courts
- multi-purpose gym
- stage
- aerobic
- dance and yoga floors
- volleyball courts
- racquetball
- squash
- and badminton courts.

COMPATIBILITY

Bona CourtLines paint will adhere to most finishes and sealers after proper preparation and dry times. ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY. Bona CourtLines paints are blendable to

achieve any custom color desired. Blending rather than tinting, maintains brightness and application characteristics.

Blending rather than tinting, maintains brightness and application characteristics.

PREPARATION

1. Sand and prepare floor using MFMA-accepted methods. 2. Make your final cut with 100 to 120-grit paper. Screen with 100-grit or 120-grit screen or use a Bona Multidisc and 80-grit or 120-grit Bona Diamond abrasives. 3. Vacuum

thoroughly. 4. Dry tack thoroughly with a dry Bona SuperCourt Microfiber Tacking Pad. 5. Apply a Bona sealer and Bona Paint as needed. (see individual product TDS for more information).

MIXING INSTRUCTIONS

Remove lid and stir thoroughly with a drill and paddle mixer.

APPLICATION

GAMELINES APPLICATION

See sealer instructions for proper sequence of sealer, gamelines and finish coats. Before applying gamelines, abrade the entire floor using 180 or 240-grit Bona Diamond abrasives mounted on 1-2 Bona Conditioning Pads. Vacuum and tack thoroughly. Note: If paint will not be applied within 24 hours, the floor must be re-abraded to ensure proper adhesion. Tape gamelines according to MFMA specifications. Apply evenly with the grain of the wood, using a brush or 1/4"-nap roller. Apply a thin coat of paint at a rate of 500-600 square feet per gallon (125-150 square feet per

quart). More than one coat may be needed. Apply second coat once first coat is dry to the touch (1-4 hours). 5. Allow paint to dry 24 hours before coating with finish. Always abrade properly dried Bona CourtLines paint double-stacked Bona Conditioning Pads. Always vacuum, and tack thoroughly with water after abrading. Allow floor to dry 30 minutes. Apply finish coat within 24 hours.

NOTE: When working with more than one quart of the same color, intermix to ensure uniform color. When mixing a custom blend, be sure to mix enough paint for the entire job to ensure uniformity



Bona CourtLines® Sport Floor Paint

OIL-MODIFIED WOOD SPORT FLOOR PAINT

Specially formulated for professional use on wooden sport floors

Bona US
24 Inverness Place East Suite 100
Englewood, CO 80112