



Bona Professional Series™ Hardwood Floor Refre...

Urethane maintenance coating formulation to restore shine to hardwood floors



A professional-level, urethane maintenance coating formulated to restore shine and luster to worn hardwood floors.

Bona Hardwood Floor Refresher® provides a clear, highly durable gloss to polyurethane finished wood floors that are dull, worn, scratched, or shows signs of wear. Bona Hardwood Floor Refresher restores the beauty of wood floors, leaves no build-up, and is recoatable.

- Urethane maintenance coating that's recoatable with finish
- Specially formulated for use on worn hardwood floors
- Restores shine
- Easy application with excellent leveling properties



Bona Professional Series™ Hardwood Floor Refre...

Urethane maintenance coating formulation to restore shine to hardwood floors

TECHNICAL DATA

Ingredient	CAS Number	Role
Water/Aqua	7732-18-5	Solvent
Acrylic Copolymer	Proprietary	Film Former
Waterborne Urethane Polymer	Proprietary	Film Former
Tributoxyethyl phosphate	78-51-3	Solvent
Ethoxydiglycol	111-90-0	Solvent
Polyethylene Wax	9002-88-4	Film Former
Modified Siloxanes	Proprietary	Surfactant
Benzoisothiazolinone	2634-33-5	Preservative
Methylisothiazolinone	2682-20-4	Preservative

pH-value:	8.0
Solids content:	10%-12%
Density:	8.39 lbs./gallon (1.01 S.G.)
US Regulatory VOC:	Does not exceed 2%
Sheen / Sheen at 60°:	(60°)>80
Dilution:	Do not dilute
Odor:	Non-offending
Color:	Milky white (when wet)
Packaging:	32 oz. bottle
Shelf life:	2-year shelf life
Application Tools:	Bona® Microfiber Applicator Pad
Coverage:	500 sq. ft. per bottle
Leveling:	Excellent
Defoaming:	Excellent
Drying time:	1 hour
Curing time:	Percent Cured After 24 hours – 90% Max. Cure – 100% after 1 week 100% after 1 week
Clean-up:	Clean all tools and equipment with warm water
Disposal:	Dispose of any remaining product in accordance with local, state, and federal regulations.

BEFORE USING, READ ALL DIRECTIONS AND MATERIAL SAFETY DATA SHEET. FOR TECHNICAL ADVICE: Call Bona US at 800-872-5515



Bona Professional Series™ Hardwood Floor Refre...

Urethane maintenance coating formulation to restore shine to hardwood floors

RECOMMENDED USE

All types of unwaxed, residential and commercial polyurethane finished wood floors that are dull, worn, scratched, or show signs of wear. Can be used on most

“aluminum oxide” and “ceramic” type UV finishes. Use every 3-4 months depending on traffic.

DIRECTIONS

BEFORE USING, READ ALL DIRECTIONS AND MATERIAL SAFETY DATA SHEET. BEFORE USING, READ ALL DIRECTIONS AND MATERIAL SAFETY DATA SHEET.

1. Remove furniture, rugs, etc. Vacuum sweep or dust mop, then thoroughly clean with Bona Hardwood Floor Cleaner and the Microfiber Cleaning Pad on your Bona Mop. Allow the floor to dry.
2. Gently rock product back and forth to mix. Slightly dampen the Microfiber Applicator Pad with water and attach to mop. Squirt product onto the floor and spread. Work in sections small enough to keep the Applicator Pad wet.

Smooth with the grain. Continue working in sections until the entire floor is finished. Rinse Applicator Pad with water.

3. Allow to dry at least 1 hour before walking on the floor. For a glossier look, a second coat may be applied after 2 hours. Allow 24 hours before heavy foot traffic.

For best results: Always test in an inconspicuous section of the floor before use. Coverage should be 500 square feet per bottle. Do not apply the product too thin or streaking will occur. Coat the entire floor to ensure an even appearance.

1. Clean
2. Squirt and Spread
3. Allow to Dry

Bona US

24 Inverness Place East, Suite 100
Englewood, Co. 80118