

Bona SuperSport Paint® - Primer

WATERBORNE PAINT PRIMER

Specially formulated for professional use on wooden sport floors



The newest addition to the Bona Sport lineup, Bona SuperSport Paint® Primer ensures superior hiding and adhesion, providing a perfect base for Bona SuperSport Paint®. GREENGUARD Gold certified and fast drying, this high-performance waterborne primer gives a consistent build-layer for any sport floor.

- Provides an even base coat for painting game lines
- Excellent hiding characteristics
- Low VOCs
- Fast drying



Bona SuperSport Paint® - Primer

WATERBORNE PAINT PRIMER

Specially formulated for professional use on wooden sport floors

TECHNICAL DATA

Ingredients:	Polymer, Water, Dipropylene glycol n butyl ether, Dipropylene glycol monoethyl ether and pigments
Density:	10 lbs./gallon
US Regulatory VOC:	< 150g/L
Odor:	Non-offending
Color:	Pale, grayish-tan
Packaging:	One-gallon pail, plastic
Shelf life:	18-month shelf life in unopened container
Storage/Transport:	Bona SuperSport Paint Primer should be stored in a climate-controlled environment. KEEP FROM FREEZING. Do not store above 100° F (38° C).
Application Tools:	Bona nanoflock roller, 1/4" nap roller
Coverage:	400-500 square feet per gallon
Leveling:	Excellent
Defoaming:	Excellent
Drying time:	3-4 hours
Clean-up:	Application tools should be cleaned with water and stored in an airtight container.
Disposal:	Dispose of contents and container in accordance with all local, regional, national, and international regulations.
Certificates:	Greenguard Gold UL 2818 - 2022 Gold Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

BEFORE USING, READ ALL DIRECTIONS AND SAFETY DATA SHEETS. FOR TECHNICAL ADVICE: Call Bona US at 800-872-5515

RESPONSE

In case of eye contact, flush immediately with water. Get medical attention if irritation occurs. For skin, wash thoroughly with soap and water. If affected by inhalation,

remove to fresh air. If swallowed, drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Get medical attention if symptoms.

RECOMMENDED USE

Basketball courts, Multi-purpose gyms, stage, aerobic, dance and yoga floors, volleyball courts, racquetball,

squash, and badminton courts.

Bona SuperSport Paint® - Primer

WATERBORNE PAINT PRIMER

Specially formulated for professional use on wooden sport floors

COMPATIBILITY

Bona SuperSport Paint Primer will adhere to most finishes and sealers after proper preparation and dry times. ALWAYS

PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY.

PREPARATION

1. Sand and prepare floor using MFMA-accepted methods. 2. Make your final cut with 100 to 120-grit paper. Screen with 100 or 120-grit screen or use a Bona MultiDisc and 80-grit or 120-grit Bona Diamond abrasives. 3. Vacuum thoroughly. 4.

Tack thoroughly with a slightly damp Bona SuperCourt® Athletic Floor Microfiber Wet Cleaning Pad. 5. Apply sealer and finish system (see finish directions).

MIXING INSTRUCTIONS

Remove lid and stir thoroughly with a drill and paddle mixer. Batch pails of the same color for maximum uniformity.

APPLICATION

See sealer instructions for proper sequence of sealer, gamelines and finish coats. Before starting the gamelines application process, abrade the entire floor using 180 or 240-grit Bona Diamond abrasives mounted on 1-2 Bona Conditioning Pads. Vacuum and tack thoroughly. NOTE: If paint will not be applied within 24 hours, the floor must be re-abraded to ensure proper adhesion. Tape gamelines according to industry standards. NOTE: To ensure crisp lines without bleed, apply Bona SuperSport Edge Guard prior to the application of Bona SuperSport Paint Primer. See product for detailed instructions. Apply Bona SuperSport Paint Primer evenly to all areas that will receive additional paint color, using a Bona NanoFlock Roller, brush or ¼"-nap roller. Apply Bona SuperSport Paint Primer at a rate of 400

square feet per gallon. More than one coat may be needed. Allow it to dry 30-90 minutes before applying final Bona SuperSport Paint color(s). High humidity and/or low temperature conditions will extend the dry time. Recommended conditions are 65-80°F and 40-60% relative humidity. If applying additional stencils or tape over freshly painted surfaces, it is recommended to wait at least 3-4 hours (under recommended conditions) before application. To ensure crisp tape lines, remove tape or stencil within 30 minutes or after 90 minutes. Additional time may be necessary when used outside of recommended climate conditions. If more than 48 hours have passed prior to subsequent coats of paint, lightly abrade the primer with a Bona Conditioning Pad.

Bona US
24 Inverness Place East Suite 100
Englewood, CO 80112