

Bona SuperSport Paint®

WATERBORNE WOOD SPORT FLOOR PAINT

Specially formulated for professional use on wooden sport floors



A fast drying, waterbased game line paint manufactured for use with both Bona® waterborne and oil-modified sport floor sealers and finishes.

Bona SuperSport Paint® is a fast drying, waterbased game line paint manufactured for use with both Bona® waterborne and oil-modified sport floor sealers and finishes. Domestically sourced pigments allow for a shelf-life of 18 months and offer better hiding.

- Fast drying with 3-4 hours recoat of finish
- No abrasion needed for adhesion of finish
- VOC compliant

Bona SuperSport Paint®

WATERBORNE WOOD SPORT FLOOR PAINT

Specially formulated for professional use on wooden sport floors

TECHNICAL DATA

Ingredients:	Polymer, Water, Dipropylene glycol n butyl ether, Dipropylene glycol monoethyl ether, and Pigments
US Regulatory VOC:	<150 g/L
Odor:	Non-offending
Packaging:	One-gallon pail, plastic
Storage/Transport:	Bona SuperSport Paint should be stored in a climate-controlled environment. KEEP FROM FREEZING. Do not store above 100° F (38° C).
Application Tools:	Bona Nanoflock roller
Coverage:	400-500 square feet per gallon
Leveling:	Excellent
Defoaming:	Excellent
Drying time:	4-6 hours (based on recommended coverage rate, under ideal conditions)
Disposal:	Dispose of any remaining product in accordance with local, state, and federal regulations.
Certificates:	Greenguard Gold UL 2818 - 2022 Gold Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

BEFORE USING, READ ALL DIRECTIONS AND SAFETY DATA SHEETS. FOR TECHNICAL ADVICE: Call Bona US at 800-872-5515

RESPONSE

In case of eye contact, flush immediately with water. Get medical attention if irritation occurs. For skin, wash thoroughly with soap and water. If affected by inhalation,

remove to fresh air. If swallowed, drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Get medical attention if symptoms occur.

RECOMMENDED USE

- Basketball courts
- multi-purpose gym
- stage
- aerobic
- dance and yoga floors
- volleyball courts
- racquetball
- squash
- and badminton courts.

Bona SuperSport Paint®

WATERBORNE WOOD SPORT FLOOR PAINT

Specially formulated for professional use on wooden sport floors

COMPATIBILITY

Bona SuperSport Paint will adhere to most finishes and sealers after proper preparation and dry times. ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE

COMPATIBILITY. Bona SuperSport Paint is blendable to achieve any custom color desired. Blending rather than tinting, maintains brightness and application characteristics

PREPARATION

SANDING AND PREPARATION OF NEW FLOORS 1. Sand and prepare floor using MFMA accepted methods. 2. Make your final cut with 100 to 120-grit paper. Screen with 100-grit or 120-grit screen or use a Bona Multidisc and 80-grit or

120-grit Bona Diamond Abrasive. 3. Vacuum thoroughly. 4. Dry tack thoroughly. 5. Apply a Bona sealer (see sealer directions for more information).

MIXING INSTRUCTIONS

Remove lid and stir thoroughly with a drill and paddle mixer. Batch pails of the same color for maximum uniformity.

APPLICATION

See sealer instructions for proper sequence of sealer, gamelines and finish coats. Before applying gamelines, abrade the entire floor using 180 or 240-grit Bona Diamond abrasives mounted on 1-2 Bona Conditioning Pads. Vacuum and tack thoroughly. NOTE: If paint will not be applied within 24 hours, the floor must be re-abraded to ensure proper adhesion. Tape gamelines according to industry standards. Apply evenly, using a Bona NanoFlock Roller, brush or 1/4"-nap roller. Apply Bona SuperSport Paint at a rate of 400-500 square feet per gallon. More than one coat may be needed. Apply any additional coats once the previous coat is dry to the touch, at least 30-90 minutes. High humidity and/or low temperature conditions will extend the dry time. Recommended conditions are 65-80°F and 40-60% relative humidity. If applying additional stencils or tape over freshly painted surfaces, it is recommended to wait at least 3-4 hours (under recommended conditions) before application. To ensure crisp tape lines, remove tape or stencil within 30

minutes or after 90 minutes. Additional time may be necessary when used outside of recommended climate conditions. To minimize multiple coats of certain colors, Bona SuperSport Light Beige can be used as a first coat primer. Allow paint to dry at least 3-4 hours (under recommended conditions) before coating with finish. When using Bona SuperSport Paint and a Bona waterborne sport finish, there is no need to abrade if coated within 48 hours. If coating with a Bona oil-modified sport finish, allow paint to dry at least 20-24 hours (under recommended conditions). Abrade SuperSport Paint with 1-2 Bona Conditioning Pads. Vacuum and tack thoroughly. Immediately apply finish coats.

NOTE: When working with more than one gallon of the same color, intermix to ensure uniform color. When mixing a custom blend, be sure to mix enough paint for the entire job to ensure uniformity.



Bona SuperSport Paint®

WATERBORNE WOOD SPORT FLOOR PAINT

Specially formulated for professional use on wooden sport floors

Bona US
24 Inverness Place East Suite 100
Englewood, CO 80112